

ZPMV2.E88441 - Wiring, Printed - Component

Wiring, Printed - Component

See General Information for Wiring, Printed - Component

TAIWAN PRINTED CIRCUIT BOARD TECHVEST CO LTD
 12 KUNG YEH 2ND RD
 PING-CHENG, TAOYUAN HSIEN 324 TAIWAN

E88441

Type	Cond Width		Cond Thk mic(mil)	SS/ DS/ DSO	Max Area Diam mm(in)	Solder		Max Oper		Flame Class	Meets UL796 DSR	C T I
	Min mm(in)	Min Edge mm(in)				C	sec	C				
Multilayer metal base printed wiring boards.												
MP-2	0.1 (0.004)	0.2 (0.008)	17 (0.67) Int:35	SS	25.4 (1.0)	288	30	110	V-0	All		0
SM-3	0.10 (0.004)	0.20 (0.008)	17 (0.67) Int:34	SS	25.4 (1.0)	288	30	125	V-0	All		3
Multilayer metal base printed wiring boards, flammability only Recognition.												
SM-2	-	-	-	SS	-	288	30	-	V-0	-		-
Multilayer printed wiring boards.												
E-0	0.075 (0.003)	0.075 (0.003)	11 (0.43) Int:34	DS	25.4 (1.0)	288	30	130	V-0	All		3
MG-0	0.05 (0.002)	0.05 (0.002)	11 (0.43) Int:34	DS	25.4 (1.0)	288	30	130	V-0	All		2
ML-0	0.05 (0.002)	0.05 (0.002)	11 (0.43) Int:68	DS	25.4 (1.0)	288	30	120	V-0	All		1
MV-0	0.05 (0.002)	0.05 (0.002)	11 (0.43) Int:68	DS	25.4 (1.0)	288	30	130	V-0	All		*
MV-0S	0.05 (0.002)	0.05 (0.002)	11 (0.43) Int:68	DS	25.4 (1.0)	288	30	130	V-0	All		*
MV-1	0.075 (0.003)	0.075 (0.003)	11 (0.43) Int:34	DS	25.4 (1.0)	288	30	130	V-1	All		-
OS-4	0.16 (0.006)	0.22 (0.009)	17 (0.67) Int:70	DS	76.2 (3.0)	260	10	105	V-0	All		-
t-0	0.075 (0.003)	0.075 (0.003)	11 (0.43) Int:34	DS	25.4 (1.0)	288	30	120	V-0	All		*
YA-1	0.08 (0.003)	0.13 (0.005)	17 (0.67) Int:68	DS	152.4 (6.0)	260	15	105	V-0	All		-
YA-2	0.08 (0.003)	0.13 (0.005)	17 (0.67) Int:68	DS	152.4 (6.0)	260	15	105	V-0	All		-
YA-3	0.13 (0.005)	0.13 (0.005)	17 (0.67) Int:68	DS	25.4 (1.0)	260	15	130	V-0	All		-
YA-3A	0.1 (0.004)	0.15 (0.006)	17 (0.67) Int:68	DS	25.4 (1.0)	260	15	130	V-0	All		-
YA-4	0.05 (0.002)	0.18 (0.007)	17 (0.67) Int:68	DS	25.4 (1.0)	288	20	130	V-0	All		-

YA-4A	0.08 (0.003)	0.18 (0.007)	17 (0.67) Int:68	DS	25.4 (1.0)	288	20	130	V-0	All	-
YAML	0.05 (0.002)	0.1 (0.004)	15 (0.59) Int:68	DS	25.4 (1.0)	288	30	130	V-0	▲	*
Single Layer Metal Base Printed Wiring Boards.											
AJ-1	0.1 (0.004)	0.2 (0.008)	34 (1.34) Int:0	SS	25.4 (1.0)	288	30	130	V-0	All	2
AJ-2	0.1 (0.004)	0.2 (0.008)	34 (1.34)	SS	25.4 (1.0)	288	30	115	V-0	All	0
AL-2	0.10 (0.004)	0.25 (0.010)	17 (0.67)	SS	25.4 (1.0)	288	30	115	V-0	All	-
CS-1	0.08 (0.003)	0.08 (0.003)	34 (1.34)	SS	25.4 (1.0)	288	30	130	V-0	All	0
CS-2	0.1 (0.004)	0.2 (0.008)	34 (1.34) Int:0	SS	25.4 (1.0)	288	30	140	V-0	All	2
D-1	0.10 (0.004)	0.29 (0.011)	35 (1.38)	SS	25.4 (1.0)	288	30	110	V-0	-	-
D-3	0.1 (0.004)	0.2 (0.008)	34 (1.34) Int:0	SS	25.4 (1.0)	288	30	150	V-0	All	3
D8-1	0.10 (0.004)	0.10 (0.004)	30 (1.18)	SS	25.4 (1.0)	288	30	120	V-0	All	0
D8-1	0.1 (0.004)	0.1 (0.004)	30 (1.18)	SS	25.4 (1.0)	288	30	120	V-0	All	0
DP-1	0.10 (0.004)	0.20 (0.008)	23 (0.91)	SS	25.4 (1.0)	288	30	130	V-0	All	4
E-2	0.075 (0.003)	0.075 (0.003)	11 (0.43)	DS	25.4 (1.0)	288	30	130	V-0	All	3
E-2	0.075 (0.003)	0.075 (0.003)	11 (0.43)	DS	25.4 (1.0)	288	30	130	V-0	All	3
HZ-1	0.14 (0.006)	0.14 (0.006)	34 (1.34)	SS	25.4 (1.0)	288	30	140	V-0	All	0
I-1	0.10 (0.004)	0.20 (0.008)	17 (0.67)	SS	25.4 (1.0)	288	30	50	V-0	All	0
K-1	0.10 (0.004)	0.30 (0.012)	34 (1.34)	SS	25.4 (1.0)	288	30	115	V-0	All	-
L-1	0.1 (0.004)	0.2 (0.008)	34 (1.34)	SS	25.4 (1.0)	288	30	90	V-0	-	-
MP-1	0.09 (0.004)	0.20 (0.008)	26 (1.02)	SS	25.4 (1.0)	288	30	90	V-0	-	-
S-1	0.1 (0.004)	0.2 (0.008)	29 (1.14)	SS	25.4 (1.0)	288	30	130	V-0	All	0
S-1	0.1 (0.004)	0.2 (0.008)	29 (1.14)	SS	25.4 (1.0)	288	30	130	V-0	All	0
S-2	0.14 (0.006)	0.14 (0.006)	34 (1.34)	SS	25.4 (1.0)	288	30	140	V-0	All	0
UN-1	0.12 (0.005)	0.2 (0.008)	34 (1.34)	SS	25.4 (1.0)	288	60	130	V-0	All	0
VT-1	0.075 (0.003)	0.25 (0.010)	17 (0.67)	SS	25.4 (1.0)	288	30	90	V-0	All	0
VT-2	0.075 (0.003)	0.20 (0.008)	17 (0.67)	SS	25.4 (1.0)	288	30	90	V-0	All	0
VT-B	0.13 (0.005)	0.13 (0.005)	17 (0.67)	SS	25.4 (1.0)	288	30	130	V-0	All	0
YXD-1	0.14 (0.006)	0.14 (0.006)	34 (1.34)	SS	25.4 (1.0)	288	30	120	V-0	All	3
Z-1	0.10 (0.004)	0.20 (0.008)	34 (1.34)	SS	25.4 (1.0)	288	30	130	V-0	All	0

Single layer metal base printed wiring boards, flammability only Recognition.											
SM-1	-	-	-	SS	-	288	30	-	V-0	-	-
Single layer printed wiring boards.											
CEM-1-S	0.075 (0.003)	0.075 (0.003)	11 (0.43)	DS	25.4 (1.0)	288	30	130	V-0	All	0
CEM-1-S	0.075 (0.003)	0.075 (0.003)	11 (0.43)	DS	25.4 (1.0)	288	30	130	V-0	All	0
CEM-3-D	0.075 (0.003)	0.075 (0.003)	11 (0.43)	DS	25.4 (1.0)	288	30	130	V-0	All	*
CEM-3-H	0.1 (0.004)	0.2 (0.008)	17 (0.67)	DS	25.4 (1.0)	260	30	130	V-0	All	*
CEM-3-N	0.075 (0.003)	0.075 (0.003)	11 (0.43)	DS	25.4 (1.0)	288	30	130	V-0	All	0
CEM-3-P	0.075 (0.003)	0.075 (0.003)	11 (0.43)	DS	25.4 (1.0)	288	30	130	V-0	All	0
CEM-3-S	0.06 (0.002)	0.075 (0.003)	11 (0.43)	DS	25.4 (1.0)	288	30	130	V-0	All	0
LC-1	0.15 (0.006)	0.15 (0.006)	17 (0.67)	DS	25.4 (1.0)	280	10	110	V-0	All	1
OS-2	0.05 (0.002)	0.05 (0.002)	11 (0.43)	DS	25.4 (1.0)	274	15	130	V-0	All	*
OS-2S	0.05 (0.002)	0.05 (0.002)	11 (0.43)	DS	25.4 (1.0)	274	15	130	V-0	All	*
OS-T	0.075 (0.003)	0.075 (0.003)	11 (0.43)	DS	25.4 (1.0)	288	30	130	V-1	All	1
t-2	0.075 (0.003)	0.075 (0.003)	11 (0.43)	DS	25.4 (1.0)	288	30	120	V-0	All	*
YA-11	0.08 (0.003)	0.13 (0.005)	17 (0.67)	DS	152.4 (6.0)	260	15	105	V-0	All	-
YADL	0.05 (0.002)	0.1 (0.004)	17 (0.67)	DS	25.4 (1.0)	288	30	130	V-0	▲	*

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or tradename "YANG AN", "tgt" or trademark   ,  *tpt* *tpts* *twt* *tmt* *tft* or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2020-05-27

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"